

DECLARATION OF PERFORMANCE

According to Regulation (EU) No.305/2011 No. GANA001/3

KOMPLEKSING S



- Unique identification code of the product-type: GANA001
- 2. Intended use/uses:

According to EN 934-2:T13, (VMA) - viscosity modifying admixture

- 3. Manufacturer:
 - ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia
- 4. Authorised representative:

1

5. System or systems of AVCP:

System 2+

6a. Harmonised standard:

EN 934-2:2009+A1:2012

Notified body:

Building Research Institute (N I S I) Ltd, 1618 Sofia, Bulgaria, №86 Nikola Petkov Blvd - notified body for construction products, with identification number NB 2032 in European Commission register performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued Certificate of conformity of the factory production control.



7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
Chloride ion content	≤ 0,1% by mass		
Alkali content	≤ 0,5% by mass		01
Corrosion behaviour	Contains components only from EN 934-1:2008, Annex A.1	1:2013	1:2012
Consistency (slump flow)	Slump flow of test mix ≥ slump flow of control mix	934-2+A1:201	934-2:2009+A1:2012
Air content	≤ 2,0%	6 N	4-2:
Segregation resistance max. segregation ≤ 70%/10 min	15% ≤ control mix ≤ 30% test mix ≤ 70% of control mix	MKC	EN 93⁄
Compressive strength	≥ 80%		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

General Manager,

Zoran Petrovski, arch.eng.



CE MARKING

Annex to DoP No. GANA001/3

 ϵ

2032

ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia

20

GANA001/3

EN 934-2:2009+A1:2012

KOMPLEKSING S

Viscosity modifying admixture

EN 934-2:T13

Chloride ion content ≤ 0,1% by mass

Alkali content ≤ 0,5% by mass

Corrosion behaviour Contains components only from EN 934-1:2008,

Annex A.1

Air content Test mix ≤ 2 % by volume above control mix

Segregation resistance

max. segregation ≤ 70%/10

min

15% ≤ control mix ≤ 30% test mix ≤ 70% of control mix

Compressive strength At 28 days: Test mix ≥ 80 % of control mix

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.