



DECLARATION OF PERFORMANCE

According to Regulation (EU) No.305/2011

No. GKDK001/3

DEKOSIL PLUS

CE

- 1. Unique identification code of the product: **GKDK001**
- Intended use/uses: According to EN 1504-2:ZA.1f, coating for surface protection and improved physical resistance of concrete.

This product is intended for:

- Physical resistance/ surface improvement Method 5.1 according to EN 1504-2 (Method 5.1 according to EN 1504-9)
- 3. Manufacturer: ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia
- 4. Authorised representative:
- 5. System or systems of AVCP: System 2+
- 6a. Harmonised standard: EN 1504-2:2004

Notified body:

Building Research Institute (N I S I) Ltd, 1618 Sofia, Bulgaria, №86 Nikola Petkov Blvd - notified body for construction products, with identification number NB 2032 in European Commission register performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued <u>Certificate of conformity of the factory production control.</u>



7. Declared performances:

Essential Characteristics	Performance	Performance Harmonised technical specification	
Adhesion strength by pull-off test	≥ 2,0 N/mm²	9	
Capillary absorption and permeability to water	w < 0,1 kg/m²·hº ^{,5}	1504-2:2006	1504-2:2004
Abrasion resistance	< 3000 mg	504	4-2:
Impact resistance	Class II ≥ 10 Nm After loading, no cracks, no delamination	N	EN 150
Reaction to fire	Class F	MKC	
Dangerous substances	No performance determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Skopje, 08.02.2024

Signed for and on behalf of the manufacturer by: General Manager, Zorah Petrovski, arch.eng.



CE MARKING

Annex to DoP No. GKDK001/3

	CE		
	2032		
ADING AD Skopje,			
	Novoselski pat (ul 1409) br.11		
1	1060 Skopje, North Macedonia		
	23		
GKDK001/3			
EN 1504-2:2004			
Coating for surface pro	DEKOSIL PLUS Detection and improved physical resistance of concrete		
Adhesion strength by pull-off test	≥ 2,0 N/mm²		
Capillary absorption and permeability to water	w < 0,1 kg/m²·h ^{0,5}		
Abrasion resistance	< 3000 mg		
Impact resistance	Class II ≥ 10 Nm		
	After loading, no cracks, no delamination		
Reaction to fire	Class F		
Dangerous substances	No performance determined		

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH) Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS). NOTE

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.